

### Overview

### HP 240 G7 Notebook PC



1. Webcam LED
2. Webcam
3. Internal microphone
4. Touchpad
5. Touchpad button
6. Power indicator LED

#### Left

7. Hard drive indicator LED
8. SD Card slot
9. USB 2.0 port
10. Security lock slot (Lock sold separately)
11. Power button

### Overview



#### Right

- |                                   |                       |
|-----------------------------------|-----------------------|
| 1. AC Smart Pin adapter plug      | 4. USB 3.1 Gen 1 port |
| 2. RJ-45/Ethernet port            | 5. USB 3.1 Gen 1 port |
| 3. HDMI port (Cable not included) | 6. Audio combo jack   |

### Overview

### AT A GLANCE

- Preinstall with Windows 10 versions, FreeDOS or Ubuntu
- Choice of 8<sup>th</sup> or 7th Generation Intel® Core™, Intel® Pentium®, or Intel® Celeron® processors
- 14" (35.56 cm) diagonal HD Anti-Glare Display
- Choice of Integrated Intel® UHD Graphics 620, HD Graphics 620, UHD Graphics 605, UHD Graphics 600 Graphics or Switchable Discrete Graphics AMD Radeon™ 520
- Dark Ash Silver color with texture pattern
- Up to 1 TB Hard Drive or 256 GB M.2 PCIe Value Solid State Drive
- Weight starting at 1.52 kg (3.4 lbs)
- Security features including FW TPM 2.0 and security lock slot (Lock not included)
- Full size textured island-style keyboard
- Touchpad with gestures support
- HP webcam with single digital microphone and HD (supporting WDR- Wide Dynamic Range) or VGA camera
- Two USB 3.1 (Gen 1) ports and One USB 2.0 port
- Wireless LAN (WLAN) up to 802.11 ac to keep you connected
- Up to 12 hours 15 mins (Intel® 7th generation CPU, HD display, Solid State Drive & 3-cell 41 WHr battery)

**NOTE: See important legal disclosures for all listed specs in their respective features sections.**

---

### Features

## PRODUCT NAME

HP 240 G7 Notebook PC

## OPERATING SYSTEM

<b>Preinstalled</b>	Windows 10 Pro 64 <sup>1</sup> Windows 10 Home 64 <sup>1</sup> Windows 10 Home Single Language 64 <sup>1</sup> Windows 10 Pro 64 (National Academic only) <sup>1,2</sup> FreeDOS Ubuntu
---------------------	--

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

## PROCESSOR

Intel® Core™ i7-8565U processor with Intel® UHD Graphics 620 (1.8 GHz base frequency, up to 4.6 GHz with Intel® Turbo Boost Technology, 8 MB cache, 4 cores)<sup>3,4,5,6</sup>

Intel® Core™ i5-8265U with Intel® UHD Graphics 620 Graphics (1.6 GHz base frequency, up to 3.9 GHz with Intel® Turbo Boost Technology, 6 MB L3 cache, 4 cores)

Intel® Core™ i7-8550U with Intel® UHD graphics 620 (1.8 GHz base frequency, up to 4 GHz with Intel® Turbo Boost Technology, 8 MB cache, 4 cores)<sup>3,4,5,6</sup>

Intel® Core™ i5-8250U with Intel® UHD Graphics 620 (1.6 GHz base frequency, up to 3.4 GHz with Intel® Turbo Boost Technology, 6 MB cache, 4 cores)<sup>3,4,5,6</sup>

Intel® Core™ i3-7020U with Intel® HD Graphics 620 (2.3 GHz, 3 MB cache, 2 cores)<sup>3,4,6</sup>

Intel® Pentium® Silver Processor N5000 with Intel® UHD Graphics 605 (1.1 GHz base frequency, up to 2.7 GHz burst frequency, 4 MB cache, 4 cores)<sup>3,4,6</sup>

Intel® Celeron® Processor N4000 with Intel® UHD Graphics 600 (1.1 GHz base frequency, up to 2.6 GHz burst frequency, 4 MB cache, 2 cores)<sup>3,4,6</sup>

### Processor Family

8th Generation Intel® Core™ i7 processor (i7-8565U, i7-8550U)<sup>6</sup>

8th Generation Intel® Core™ i5 processor (i5-8265U, i5-8250U)<sup>6</sup>

7th Generation Intel® Core™ i3 processor (i3-7020U)<sup>6</sup>

Intel® Pentium® processor (N5000 is Windows 10 only)<sup>6</sup>

Intel® Celeron® processor (N4000 is Windows 10 only)<sup>6</sup>

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

### Features

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
5. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.
6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

### CHIPSET

Intel® SOC Chipset

### GRAPHICS

#### Integrated

Intel® UHD Graphics 620<sup>7</sup>

Intel® HD Graphics 620<sup>7</sup>

Intel® UHD Graphics 605<sup>7</sup>

Intel® UHD Graphics 600<sup>7</sup>

#### Discrete

AMD Radeon™ RX 520 (2 GB GDDR5 dedicated)<sup>8</sup>

#### Supports

Support HD decode, DX12, HDMI 1.4b<sup>9</sup>

7. HD content required to view HD images.
8. AMD Dynamic Switchable Graphics technology requires an Intel processor, plus an AMD Radeon™ discrete graphics configuration and is not available on FreeDOS and Linux OS. With AMD Dynamic Switchable Graphics technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).
9. HDMI cable sold separately.

### DISPLAY

#### Internal

##### Non-Touch

35.56 cm (14") diagonal HD SVA eDP anti-glare WLED-backlit slim-flat, 220 cd/m<sup>2</sup>, 45% NTSC (1366 x 768)<sup>7,10</sup>

#### HDMI

Port supports resolutions up to 1920 x 1200 external resolution @60 Hz

7. HD content required to view HD images.
10. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

### Features

## STORAGE AND DRIVES

### Primary Storage

1 TB 5400 rpm SATA<sup>11</sup>  
500 GB 7200 rpm SATA<sup>11</sup>  
500 GB 5400 rpm SATA<sup>11</sup>

### Primary M.2 Storage

128 GB M.2 SATA-3 TLC Solid State Drive<sup>11</sup>  
256 GB M.2 SATA-3 TLC Solid State Drive<sup>11</sup>  
256 GB PCIe® NVMe™ M.2 Value Solid State Drive<sup>11</sup>

11. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

## MEMORY

### Standard

#### Maximum Memory

16 GB DDR4-2400 SDRAM<sup>12</sup>  
16 GB DDR4-2133 SDRAM<sup>12</sup>

#### Memory

16 GB DDR4-2400 SDRAM (2 X 8 GB)<sup>12</sup>  
12 GB DDR4-2400 SDRAM (4 GB + 8 GB)<sup>12</sup>  
8 GB DDR4-2400 SDRAM (1 x 8 GB)  
8 GB DDR4-2400 SDRAM (2 x 4 GB)<sup>12</sup>  
4 GB DDR4-2400 SDRAM (1 x 4 GB)  
16 GB DDR4-2133 SDRAM (2 X 8 GB)<sup>12</sup>  
12 GB DDR4-2133 SDRAM (4 GB + 8 GB)<sup>12</sup>  
8 GB DDR4-2133 SDRAM (1 x 8 GB)  
8 GB DDR4-2133 SDRAM (2 x 4 GB)<sup>12</sup>  
4 GB DDR4-2133 SDRAM (1 x 4 GB)

#### Memory Slots

2 SODIMM (Intel® 8th & 7th Generation Intel® Core™ processor)  
DDR4 PC4 SODIMMS, system runs at 2400 (Intel 7th Gen (KBL) runs at 2133)  
Supports Dual Channel Memory  
1 SODIMM (Intel® Pentium®, Celeron® processors)  
All slots are customer non-accessible / non-upgradeable

**NOTE:** All slots are customer non-accessible / non-upgradeable.

12. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

### Features

## NETWORKING/COMMUNICATIONS

### WLAN

Realtek 802.11ac (2x2) WLAN and Bluetooth® 4.2 Combo (MU-MIMO supported)<sup>13</sup>

Realtek 802.11ac (1x1) WLAN and Bluetooth® 4.2 Combo (MU-MIMO supported)<sup>13</sup>

Realtek 802.11b/g/n (1x1) and Bluetooth® 4.2 Combo<sup>13</sup>

### Miracast

Compatible with Miracast-certified devices<sup>14</sup>

### Ethernet

Integrated 10/100/1000 GbE NIC<sup>15</sup>

13. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited.

14. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

15. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

## AUDIO/MULTIMEDIA

### Audio

2 Integrated stereo speakers

### Camera

HP TrueVision HD Camera<sup>7,16</sup>

### Webcam

VGA webcam<sup>16,17</sup>

7. HD content required to view HD images.

16. Sold separately or as an optional feature.

17. Internet access required.

## KEYBOARDS/TOUCHPAD

### Keyboard

Full size island-style keyboard

### Pointing Device

Touchpad with multi-touch gesture support

### Function Keys

F1 - Open "How to get help in Windows 10" webpage

F2 - Brightness Down

F3 - Brightness Up

F4 - Display Switching

F5 - Blank

F6 - Mute

F7 - Volume Down

F8 - Volume Up

F9 - Previous

F10 - Play/Pause

F11 - Next

### Features

F12 - Airplane mode

## SOFTWARE AND SECURITY

### Preinstalled Software

HP JumpStart  
HP Documentation  
HP Setup Integrated OOBE  
HP SSRM  
HP Audio Switch  
HP Support Assistant <sup>18</sup>  
McAfee LiveSafe™

### Security Management

TPM 2.0<sup>19</sup>  
Security lock slot (Lock sold separately)

18. HP Support Assistant requires Windows and Internet access.

19. Firmware TPM is version 2.0. Hardware TPM is v1.2, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT).

## POWER

### Power Supply

HP Smart 65 W External AC power adapter <sup>20,22</sup>  
HP Smart 65 W EM External AC power adapter <sup>20,22</sup>  
HP Smart 45 W External AC power adapter <sup>20</sup>

### Primary Battery

HP Long Life 3-cell, 41 Wh Li-ion <sup>21</sup>  
Support battery fast charging - Approximately 90% in 90 minutes<sup>22</sup>

### Battery Life

Up to 12 hours 15 mins (Intel® 7th generation CPU, HD display, Solid State Drive & 3-cell 41 WHr battery) <sup>23</sup>

### Power Cord

1M (3.28 feet) length power cord

### Battery Weight

0.18 kg  
0.39 lb

20. Availability may vary by country.

21. Battery is internal and not replaceable by customer. Serviceable by warranty.

22. Recharges the battery up to 90% within 90 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 90% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.



### Features

23. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

---

## WEIGHTS & DIMENSIONS

### Product Weight

Starting at 3.3 lbs<sup>24</sup>

Starting at 1.52 kg<sup>24</sup>

### Product Dimensions (W x D x H)

13.19 x 9.21 x 0.78 in

33.5 x 23.4 x 1.99 cm

24. Weight will vary by configuration.

---

### Features

## PORTS/SLOTS

### Ports/Connectors

- 2 USB 3.1 Gen 1
- 1 USB 2.0
- 1 HDMI v1.4b<sup>9</sup>
- 1 RJ-45
- 1 AC power
- 1 Headphone/microphone combo jack

### Expansion Slots

- 1 multi-format digital media reader
- Supports SD, SDHC, SDXC

9. HDMI cable sold separately.

---

## SERVICE AND SUPPORT

HP Services offers 1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.<sup>25</sup>

25. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

---

### Technical Specifications

#### SYSTEM UNIT

##### Stand-Alone Power Requirements

###### (AC Power)

Nominal Operating Voltage	19.5 V
Average Operating Power	Win 10
Integrated graphics	7.69W
Max Operating Power	Discrete < 65W UMA < 45W

##### Temperature

Operating	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
Non-operating	-4° to 140° F (-20° to 60° C)

##### Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%

##### Shock

Operating	40 G, 2 ms duration, half-sine
Non-operating	240 G, 2 ms duration, half-sine

##### Random Vibration

Operating	1.043 grms
Non-operating	3.5 grms

##### Planned Industry Standard

###### Certifications

UL	Yes
CSA	No
FCC Compliance	Yes
ENERGY STAR®	Yes <sup>26</sup>
EPEAT® 2019	Yes, Silver in U.S. <sup>27</sup>
ICES	Yes
Australia /	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes

### Technical Specifications

26. Configurations of the HP 240 G7 that are ENERGY STAR® certified<sup>2</sup> are identified as HP 240 G7 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

27. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit <http://www.epeat.net> for more information.

### Technical Specifications

#### DISPLAYS

<b>14" HD WLED Anti-Glare diagonal (1366 x 768) slim-flat (3.0mm), SVA, eDP</b>	<b>Outline Dimensions (W x H x D)</b>	320.9 x 250.6 x 3.0
	<b>Active Area</b>	309.5 x 174.05
	<b>Weight</b>	270g max
	<b>Diagonal Size</b>	14.0 (inch)
	<b>Thickness</b>	3.0 (mm) max
	<b>Interface</b>	eDP 1.2
	<b>Surface Treatment</b>	AG
	<b>Contrast Ratio</b>	600:1 (typ. AG)
	<b>Refresh Rate</b>	60Hz
	<b>Brightness</b>	220nits typical
	<b>Pixel Resolution</b>	1366 x 768 (HD)
	<b>Format of LCD Pixel Arrangement</b>	RGB
	<b>Backlight</b>	LED
	<b>Color Gamut Coverage</b>	45% of NTSC
<b>Color Depth</b>	6 bits	
<b>Viewing Angle</b>	45/45/20/40	

### Technical Specifications

#### STORAGE AND DRIVES

<b>500 GB 5400 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	92g(0.20lb)
	<b>Rotation speed</b>	5400 rpm
	<b>Cache Buffer</b>	Up to 128MB
	<b>Height</b>	7.0 +/- 0.2 mm (0.28 +/- .008 in)
	<b>Width</b>	69.85 +/- 0.25 mm (2.750 +/- 0.010 in)
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Transfer Rate</b>	600 MB/s
	<b>Seek Time</b>	Single Track: 2 ~ 1.5 ms Average: 11 ~ 16 ms Maximum: 18 ~ 22 ms
	<b>Logical Blocks</b>	976,773,168
	<b>Operating Temperature</b>	0° to 60°C
	<b>Security Features</b>	ATA Security
	<b>Features</b>	S.M.A.R.T., NCQ, Ultra DMA

<b>500 GB 7200 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	92g(0.20lb)
	<b>Rotation speed</b>	7200 rpm
	<b>Cache Buffer</b>	Up to 128MB
	<b>Height</b>	7.0 +/- 0.2 mm (0.28 +/- .008 in)
	<b>Width</b>	69.85 +/- 0.25 mm (2.750 +/- 0.010 in)
	<b>Interface</b>	ATA-8, SATA 3.0
	<b>Transfer Rate</b>	Single Track: 2 ~ 1.5 ms; Average: 11 ~ 13 ms; Maximum: 18 ~ 22 ms
	<b>Seek Time</b>	976,773,168
	<b>Logical Blocks</b>	0° to 60°C
	<b>Operating Temperature</b>	ATA Security
	<b>Security Features</b>	S.M.A.R.T., NCQ, Ultra DMA
	<b>Features</b>	976,773,168

<b>1 TB 5400 rpm SATA Hard Drive</b>	<b>Drive Weight</b>	90g(0.198lb)
	<b>Rotation speed</b>	5400 rpm
	<b>Cache Buffer</b>	Up to 128MB
	<b>Height</b>	<7.2mm
	<b>Width</b>	69.85 +/- 0.25 mm (2.750 +/- 0.010 in)
	<b>Interface</b>	ATA-8, SATA 3.0

### Technical Specifications

<b>Transfer Rate</b>	600 MB/s
<b>Seek Time</b>	Single Track: 2 ~ 1.5 ms; Average: 11 ~ 16 ms; Maximum: 18 ~ 22 ms
<b>Logical Blocks</b>	976,773,168
<b>Operating Temperature</b>	0° to 60°C
<b>Security Features</b>	ATA Security
<b>Features</b>	S.M.A.R.T., NCQ, Ultra DMA

#### 128 GB 2280 M2 SATA-3 TLC Solid State Drive

<b>Drive Weight</b>	0.02 lb (10 g)
<b>NAND Type/Size</b>	TLC/128GB
<b>Height</b>	0.09 in (2.3 mm)
<b>Width</b>	0.87 in (22 mm)
<b>Interface</b>	ATA-8, SATA 3.0
<b>Transfer Rate</b>	550MB/s
<b>Logical Blocks</b>	250,069,680
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Security Features</b>	ATA Security
<b>Features</b>	DIPM; TRIM; DEVSLP

#### 256 GB 2280 M2 SATA-3 TLC Solid State Drive

<b>Drive Weight</b>	0.02 lb (10 g)
<b>Height</b>	0.09 in (2.3 mm)
<b>Width</b>	0.87 in (22 mm)
<b>Interface</b>	ATA-8, SATA 3.0
<b>Transfer Rate</b>	550MB/s
<b>Logical Blocks</b>	500,118,192
<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
<b>Security Features</b>	ATA Security
<b>Features</b>	DIPM; TRIM; DEVSLP

### Technical Specifications

<b>256 GB 2280 M2 PCIe NVMe Value Solid State Drive</b>	<b>Form Factor</b>	M.2 2280
	<b>Capacity</b>	256 GB
	<b>NAND Type</b>	TLC
	<b>Height</b>	0.09 in (2.3 mm)
	<b>Width</b>	0.87 in (22 mm)
	<b>Weight</b>	0.01 lb (6 g) ~ 0.02 lb (10 g)
	<b>Interface</b>	PCIe NVMe Gen3x2
	<b>Maximum Sequential Read</b>	Up To 1500 MB/s
	<b>Maximum Sequential Write</b>	Up To 1000 MB/s
	<b>Logical Blocks</b>	500,118,192
	<b>Operating Temperature</b>	32° to 158°F (0° to 70°C) [ambient temp]
	<b>Features</b>	DIPM; TRIM; DEVSLP

<b>16 GB Intel Optane Solution PCIe Gen3x2 M.2 SSD</b>	Form Factor	M.2 2280
	Capacity	16 GB
	NAND Type	3D Xpoint
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	PCIe NVMe Gen3x2
	Maximum Sequential Read	1350MB/s
	Maximum Sequential Write	290MB/s
	Logical Blocks	31,257,387
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]

## NETWORKING/COMMUNICATIONS

### WLAN

<b>Realtek RTL8822BE 802.11 ac 2x2 WLAN and Bluetooth® 4.2 Combo Adapter (MU-MIMO supported)</b>	<b>Wireless LAN Standards</b>	IEEE 802.11a
		IEEE 802.11b
		IEEE 802.11g
		IEEE 802.11n
		IEEE 802.11ac
	<b>Interoperability</b>	Wi-Fi® certified
	<b>Frequency Band</b>	802.11b/g/n
		• 2.402 – 2.482 GHz
		802.11a/n
		• 4.9 – 4.95 GHz (Japan)
• 5.15 – 5.25 GHz		



### Technical Specifications

	<ul style="list-style-type: none"> <li>• 5.25 – 5.35 GHz</li> <li>• 5.47 – 5.725 GHz</li> <li>• 5.825 – 5.850 GHz</li> </ul>
<b>Data Rates</b>	<ul style="list-style-type: none"> <li>• 802.11b: 1, 2, 5.5, 11 Mbps</li> <li>• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps</li> <li>• 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz)</li> <li>• 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)</li> </ul>
<b>Modulation</b>	<p>Direct Sequence Spread Spectrum                      BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM</p>
<b>Security<sup>3</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and WiFi® compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• IEEE 802.11i</li> <li>• Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>• WAPI</li> </ul>
<b>Network Architecture Models</b>	<p>Ad-hoc (Peer to Peer)                      Infrastructure (Access Point Required)</p>
<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b: +14dBm minimum</li> <li>• 802.11g: +12dBm minimum</li> <li>• 802.11a: +12dBm minimum</li> <li>• 802.11n HT20(2.4GHz): +12dBm minimum</li> <li>• 802.11n HT40(2.4GHz): +12dBm minimum</li> <li>• 802.11n HT20(5GHz): +10dBm minimum</li> <li>• 802.11n HT40(5GHz): +10dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +10dBm minimum</li> </ul>
<b>Power Consumption</b>	<p>Transmit mode: 2.0 W                      Receive mode: 1.6 W                      Idle mode (PSP)180 mW (WLAN Associated)                      Idle mode: 50 mW (WLAN unassociated)                      Connected Standby/Modern Standby: 10mW                      Radio disabled: 8 mW</p>
<b>Power Management</b>	<p>ACPI and PCI Express compliant power management                      802.11 compliant power saving mode</p>
<b>Receiver Sensitivity<sup>3</sup></b>	<p>802.11b, 1Mbps: -93.5dBm maximum                      802.11b, 11Mbps: -84dBm maximum                      802.11a/g, 6Mbps: -86dBm maximum                      802.11a/g, 54Mbps: -72dBm maximum                      802.11n, MCS07: -67dBm maximum                      802.11n, MCS15: -64dBm maximum                      802.11ac, MCS0: -84dBm maximum</p>

### Technical Specifications

<b>Antenna type</b>	802.11ac, MCS9: -59dBm maximum High efficiency antenna with spatial diversity, mounted in the display enclosure
<b>Form Factor</b>	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications PCI-Express M.2 MiniCard
<b>Dimensions</b>	Type 2230: 2.3 x 22.0 x 30.0 mm
<b>Weight</b>	Type 2230: 2.8g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
<b>Altitude</b>	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED White – Radio ON

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

<b>Bluetooth® Specification</b>	4.0/4.1/4.2 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Signaling Data Rate</b>	Legacy: 3 Mbps Signaling data rate <sup>1</sup> BLE: 1 Mbps Signaling data rate <sup>1</sup> <ol style="list-style-type: none"> <li>1. Actual throughput may vary.</li> </ol>
<b>Transmit Power</b>	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels  Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)  The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

### Technical Specifications

<b>Realtek RTL8723DE 802.11 bgn (1x1) WLAN and Bluetooth® 4.2 Combo Adapter</b>	<b>Wireless LAN Standards</b>	IEEE 802.11b IEEE 802.11g IEEE 802.11n
	<b>Interoperability</b>	Wi-Fi® certified
	<b>Frequency Band</b>	802.11b/g/n • 2.402 – 2.482 GHz
	<b>Data Rates</b>	• 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 7, (20MHz, and 40MHz)
	<b>Modulation</b>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM
	<b>Security<sup>3</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and Wi-Fi® compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• IEEE 802.11i</li> <li>• Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>• WAPI</li> </ul>
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b: +14dBm minimum</li> <li>• 802.11g: +12dBm minimum</li> <li>• 802.11n HT20(2.4GHz): +12dBm minimum</li> <li>• 802.11n HT40(2.4GHz): +12dBm minimum</li> </ul>
	<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> <li>• Idle mode (PSP)180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode	
<b>Receiver Sensitivity<sup>3</sup></b>	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11g, 6Mbps: -86dBm maximum 802.11g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum	
<b>Antenna type</b>	High efficiency antenna.	

One embedded dual band 2.4/5 GHz antenna is provided to the card to

### Technical Specifications

	support WLAN communications and Bluetooth communications	
<b>Form Factor</b>	PCI-Express M.2 MiniCard	
<b>Dimensions</b>	Type 2230: 2.3 x 22.0 x 30.0 mm	
<b>Weight</b>	Type 2230: 2.8g	
<b>Operating Voltage</b>	3.3v +/- 9%	
<b>Temperature</b>	Operating	14° to 158° F (–10° to 70° C)
	Non-operating	–40° to 176° F (–40° to 80° C)
<b>Humidity</b>	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
<b>Altitude</b>	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED White – Radio ON	

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

<b>Bluetooth® Specification</b>	4.0/4.1/4.2 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
<b>Signaling Data Rate</b>	Legacy: 3 Mbps Signaling data rate <sup>1</sup> BLE: 1 Mbps Signaling data rate <sup>1</sup> <ol style="list-style-type: none"> <li>1. Actual throughput may vary.</li> </ol>
	Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels
	Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

### Technical Specifications

<b>Realtek RTL8821CE 802.11 ac 1x1 WLAN and Bluetooth® 4.2 Combo Adapter (MU-MIMO supported)</b>	<b>Wireless LAN Standards</b>	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac
	<b>Interoperability</b>	Wi-Fi® certified
	<b>Frequency Band</b>	802.11b/g/n •2.402 – 2.482 GHz
		802.11a/n •4.9 – 4.95 GHz (Japan) •5.15 – 5.25 GHz •5.25 – 5.35 GHz •5.47 – 5.725 GHz •5.825 – 5.850 GHz
	<b>Data Rates</b>	•802.11b: 1, 2, 5.5, 11 Mbps •802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps •802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) •802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
	<b>Modulation</b>	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
	<b>Security<sup>3</sup></b>	<ul style="list-style-type: none"> <li>• IEEE and Wi-Fi® compliant 64 / 128 bit WEP encryption for a/b/g mode only</li> <li>• AES-CCMP: 128 bit in hardware</li> <li>• 802.1x authentication</li> <li>• WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</li> <li>• WPA2 certification</li> <li>• IEEE 802.11i</li> <li>• Cisco Certified Extensions, all versions through CCX4 and CCX Lite</li> <li>• WAPI</li> </ul>
	<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	<b>Roaming</b>	IEEE 802.11 compliant roaming between access points
	<b>Output Power<sup>2</sup></b>	<ul style="list-style-type: none"> <li>• 802.11b: +14dBm minimum</li> <li>• 802.11g: +12dBm minimum</li> <li>• 802.11a: +12dBm minimum</li> <li>• 802.11n HT20(2.4GHz): +12dBm minimum</li> <li>• 802.11n HT40(2.4GHz): +12dBm minimum</li> <li>• 802.11n HT20(5GHz): +10dBm minimum</li> <li>• 802.11n HT40(5GHz): +10dBm minimum</li> <li>• 802.11ac VHT80(5GHz): +10dBm minimum</li> </ul>
	<b>Power Consumption</b>	<ul style="list-style-type: none"> <li>• Transmit mode 2.0 W</li> <li>• Receive mode 1.6 W</li> </ul>

### Technical Specifications

	<ul style="list-style-type: none"> <li>• Idle mode (PSP) 180 mW (WLAN Associated)</li> <li>• Idle mode 50 mW (WLAN unassociated)</li> <li>• Connected Standby 10mW</li> <li>• Radio disabled 8 mW</li> </ul>
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>3</sup></b>	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
<b>Antenna type</b>	High efficiency antenna.  One embedded dual band 2.4/5 GHz antenna is provided to the card to support WLAN communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	Type 2230: 2.3 x 22.0 x 30.0 mm
<b>Weight</b>	Type 2230: 2.8g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
<b>Altitude</b>	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED White – Radio ON

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

#### HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

<b>Bluetooth® Specification</b>	4.0/4.1/4.2 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz
<b>Number of Available Channels</b>	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)

### Technical Specifications

<b>Signaling Data Rate</b>	<p>Legacy: 3 Mbps Signaling data rate<sup>1</sup>            BLE: 1 Mbps Signaling data rate<sup>1</sup>            1. Actual throughput may vary.</p>												
	<p>Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels</p>												
	<p>Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)</p>												
<b>Transmit Power</b>	<p>The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.</p>												
<b>Realtek Ethernet (10/100/1000)</b>	<table border="0"> <tr> <td data-bbox="371 831 587 863"><b>Ethernet Features</b></td> <td data-bbox="687 831 1520 1251"> <p>10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)            100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)            1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40)            Auto-Negotiation (Automatic Speed Selection)            Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s            IEEE 802.1p QoS (Quality of Service) Support            IEEE 802.1q VLAN support            IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)            IEEE 802.3az EEE (Energy Efficient Ethernet)            Jumbo Frame 9K            Auto MDI/MDIX Crossover cable detection</p> </td> </tr> <tr> <td data-bbox="371 1262 608 1293"><b>Power Management</b></td> <td data-bbox="687 1262 1390 1398"> <p>ACPI compliant - multiple power modes            Situation-sensitive features reduce power consumption            Advanced link down power saving for reducing link down power consumption</p> </td> </tr> <tr> <td data-bbox="371 1409 635 1440"><b>Performance Features</b></td> <td data-bbox="687 1409 1182 1545"> <p>TCP/IP/UDP Checksum Offload (configurable)            Protocol Offload (ARP &amp; NS)            Large send offload and Giant send offload            Receiving Side Scaling</p> </td> </tr> <tr> <td data-bbox="371 1556 544 1587"><b>Manageability</b></td> <td data-bbox="687 1556 1520 1797"> <p>Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)            PXE 2.1 Remote Boot            Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)            Comprehensive diagnostic and configuration software suite            Virtual Cable Doctor for Ethernet cable status</p> </td> </tr> <tr> <td data-bbox="371 1808 488 1839"><b>Interface</b></td> <td data-bbox="687 1808 1078 1839"> <p>PCI Express 1.1 to support ASPM L1</p> </td> </tr> <tr> <td data-bbox="371 1850 647 1881"><b>NIC Device Driver Name</b></td> <td data-bbox="687 1850 1174 1881"> <p>Realtek PCIe GBE Ethernet Family Controller</p> </td> </tr> </table>	<b>Ethernet Features</b>	<p>10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)            100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)            1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40)            Auto-Negotiation (Automatic Speed Selection)            Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s            IEEE 802.1p QoS (Quality of Service) Support            IEEE 802.1q VLAN support            IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)            IEEE 802.3az EEE (Energy Efficient Ethernet)            Jumbo Frame 9K            Auto MDI/MDIX Crossover cable detection</p>	<b>Power Management</b>	<p>ACPI compliant - multiple power modes            Situation-sensitive features reduce power consumption            Advanced link down power saving for reducing link down power consumption</p>	<b>Performance Features</b>	<p>TCP/IP/UDP Checksum Offload (configurable)            Protocol Offload (ARP &amp; NS)            Large send offload and Giant send offload            Receiving Side Scaling</p>	<b>Manageability</b>	<p>Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)            PXE 2.1 Remote Boot            Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)            Comprehensive diagnostic and configuration software suite            Virtual Cable Doctor for Ethernet cable status</p>	<b>Interface</b>	<p>PCI Express 1.1 to support ASPM L1</p>	<b>NIC Device Driver Name</b>	<p>Realtek PCIe GBE Ethernet Family Controller</p>
<b>Ethernet Features</b>	<p>10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)            100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)            1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40)            Auto-Negotiation (Automatic Speed Selection)            Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s            IEEE 802.1p QoS (Quality of Service) Support            IEEE 802.1q VLAN support            IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)            IEEE 802.3az EEE (Energy Efficient Ethernet)            Jumbo Frame 9K            Auto MDI/MDIX Crossover cable detection</p>												
<b>Power Management</b>	<p>ACPI compliant - multiple power modes            Situation-sensitive features reduce power consumption            Advanced link down power saving for reducing link down power consumption</p>												
<b>Performance Features</b>	<p>TCP/IP/UDP Checksum Offload (configurable)            Protocol Offload (ARP &amp; NS)            Large send offload and Giant send offload            Receiving Side Scaling</p>												
<b>Manageability</b>	<p>Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)            PXE 2.1 Remote Boot            Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30)            Comprehensive diagnostic and configuration software suite            Virtual Cable Doctor for Ethernet cable status</p>												
<b>Interface</b>	<p>PCI Express 1.1 to support ASPM L1</p>												
<b>NIC Device Driver Name</b>	<p>Realtek PCIe GBE Ethernet Family Controller</p>												

### Technical Specifications

#### POWER

<b>HP 65W Smart AC adapter</b>	<b>Dimensions (H x W x D)</b>	108 x 47 x 37.4mm	
	<b>Weight</b>	250 g	
	<b>Input</b>	100 to 240 VAC	
		<b>Input Efficiency</b>	88.0 % at 115 VAC and 89.0 % at 230VAC
	<b>Output</b>	<b>Input frequency range</b>	50~ 60 Hz
		<b>Input AC current</b>	Max. 1.7 A at 90 VAC
		<b>Output power</b>	65W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	5ms at 115 VAC input
		<b>Output current limit</b>	The power supply shall limit the maximum steady state output current to an average current of 11 Amperes.
		<b>Connector</b>	4.5mm Barrel Type,
	<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°C to 35° C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°C to 85°C)
		<b>Altitude</b>	-4°F to 185°F (-20°C to 85°C)
		<b>Humidity</b>	The power supply can be operated at 5,000 m above sea level
<b>Storage Humidity</b>			
<b>EMI and Safety Certifications</b>	*CE Mark - full compliance with LVD and EMC directives		
	* Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.		
	* MTBF - over 200,000 hours at 25°C ambient condition.		
<b>45 W AC adapter</b>	<b>Dimensions (H x W x D)</b>	95 x 40 x 26.5mm	
	<b>Weight</b>	200 g	
	<b>Input</b>	100 to 240 VAC	
		<b>Input Efficiency</b>	87.8 % at 115 VAC and 88.5 % at 230VAC
	<b>Output</b>	<b>Input frequency range</b>	50~ 60 Hz
		<b>Input AC current</b>	Max. 1.4 A at 90 VAC
		<b>Output power</b>	45W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	5ms at 115 Vac input
		<b>Output current limit</b>	The power supply shall limit the maximum steady state output current to an average current of 8 Amperes.
		<b>Connector</b>	4.5mm Barrel Type
	<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°C to 35° C)



### Technical Specifications

		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°C to 85°C)
		<b>Altitude</b>	-4°F to 185°F (-20°C to 85°C)
		<b>Humidity</b>	The power supply can be operated at 5,000 m above sea level
		<b>Storage Humidity</b>	
	<b>EMI and Safety Certifications</b>		*CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.
<b>HP 65 W Smart AC adapter (EM)</b>	<b>Dimensions (H x W x D)</b>		102 x 55 x 30mm
	<b>Weight</b>		270 g
	<b>Input</b>		100 to 240 VAC
		<b>Input Efficiency</b>	88.0 % at 115 VAC and 89.0 % at 230VAC
		<b>Input frequency range</b>	50~ 60 Hz
		<b>Input AC current</b>	Max. 1.7 A at 90 VAC
	<b>Output</b>	<b>Output power</b>	65W
		<b>DC output</b>	19.5V
		<b>Hold-up time</b>	5ms at 115 Vac input
		<b>Output current limit</b>	The power supply shall limit the maximum steady state output current to an average current of 11 Amperes.
	<b>Connector</b>		4.5mm Barrel Type,
	<b>Environmental Design</b>	<b>Operating temperature</b>	32°F to 95°F (0°C to 35° C)
		<b>Non-operating (storage) temperature</b>	-4°F to 185°F (-20°C to 85°C)
		<b>Altitude</b>	The power supply can be operated at 5,000 m above sea level
		<b>Humidity</b>	The power supply shall withstand without degradation with 95% relative humidity, non-condensing, both operating and non-operating.
		<b>Storage Humidity</b>	
	<b>EMI and Safety Certifications</b>		*CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.
<b>HP 3-cell Li-Ion Long Life - Fast Charge (41 WHr)</b>	<b>Dimensions (H x W x L)</b>		6.0 x 186.85 x 90.2 mm (0.236 x 7.35 x 3.55 inch)
	<b>Weight</b>		0.18 kg (0.39 lb)
	<b>Cells/Type</b>		3cell Lithium-Ion Polymer cell / 515974
	<b>Voltage</b>		11.4V

### Technical Specifications

<b>Amp-hour capacity</b>	3.6Ah
<b>Watt-hour capacity</b>	41Wh
<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
<b>Operating (Discharging)</b>	14° to 122° F (-10° to 60° C)
<b>Optional Travel Battery Available</b>	No

<b>HP 3-cell Li-Ion Long Life - Fast Charge (41 WHr)</b>	<b>Dimensions</b>	6.0 x 186.85 x 90.2 mm (0.236 x 7.35 x 3.55 inch)
	<b>Weight</b>	0.19 kg (0.41 lb)
	<b>Cells/Type</b>	3cell Lithium-Ion Prismatic cell / 496080
	<b>Voltage</b>	11.55V
	<b>Amp-hour capacity</b>	3.615Ah/3.63Ah
	<b>Watt-hour capacity</b>	41Wh
	<b>Operating (Charging)</b>	32° to 113° F (0° to 45° C)
	<b>Operating (Discharging)</b>	14° to 122° F (-10° to 60° C)
	<b>Optional Travel Battery Available</b>	No

Options and Accessories (sold separately and availability may vary by country)

Category	Description	Part Number
<b>Cases</b>	HP Essential Top Load Case	H2W17AA#xxx
	HP Essential Backpack (up to 15.6")	H1D24AA
	HP Essential Messenger Case (up to 17.3")	H1D25AA
<b>Docking</b>	HP 3005PR USB3 Port Replicator	Y4H06AA
	HP USB Travel Dock	TOK30AA
<b>Input/Output</b>	HP Slim USB Keyboard and Mouse	T6T83AA
	HP Slim Wireless Keyboard and Mouse	T6L04AA
	HP 3-Button USB Laser Mouse	H4B81AA
	HP USB Travel Mouse	G1K28AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP Ultra Mobile Wireless Mouse	H6F25AA#xxx
	HP HDMI to DVI Adapter	F5A28AA
<b>Power</b>	HP 45W Smart AC Adapter 4.5mm	H6Y88AA#XXX
	HP 65W Smart AC Adapter	H6Y89AA#xxx
	HP 65W Slim AC Adapter	H6Y82AA#xxx
<b>Storage</b>	HP External USB Optical Drive	F2B56AA
<b>Memory</b>	HP 4GB 2666Mhz DDR4	4VN05AA
	HP 8GB 2666Mhz DDR4	4VN06AA
<b>UCC</b>	HP Stereo USB Headset	T1A67AA
	HP Stereo 3.5mm Headset	T1A66AA
	HP UC Wired Headset	K7V17AA
<b>Displays</b>	HP S140u 14-inch Portable Display	G8R65AA
	HP ProDisplay P223 21.5-inch Monitor	X7R61AA
	HP ProDisplay P232 23-inch Monitor	K7X31AA
	HP ProDisplay P240va 23.8-inch Monitor	N3H14AA
	HP EliteDisplay S14 14-inch USB-C Portable Monitor	3HX46AA

### Summary of Changes

<b>Date of change:</b>	<b>Version History:</b>		<b>Description of change:</b>
March 1, 2019	From v1 to v2	Removed	USB-C Travel Dock
March 4, 2019	From v2 to v3	removed	Battery Life
March 25, 2019	From v3 to v4	Added	Battery Life
May 17, 2019	From v4 to v5	Updated	Battery Life
June 13, 2019	From v5 to v6	Updated	EPEAT
July 2, 2019	From v6 to v7	Updated	Battery Life
July 5, 2019	From v7 to v8	Updated	Color Gamut
September 6, 2019	From v8 to v9	Updated	i5-8265U and i7-8565U Processors

Copyright © 2019 Hewlett Packard Development Company, L.P.

The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core and Celeron are trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark of its proprietor used by HP Inc. under license. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.